TECPEL

HIGH VOLTAGE & HIGH FREQUENCE OSCILLOSCOPE PROBE




HVP-15HF

VERY LOW NOISE & HIGH EMS

- MAX. VOLTAGE:15KV DC.
- BANDWIDTH:DC~50MHz.
- DIVISION RATIO:X1000.
- SIGNAL / NOISE:>60dB(1KHz)

TECPEL

HIGH VOLTAGE & HIGH FREQUENCE OSCILLOSCOPE PROBE



HVP-15HF

SPECIFICATION	
MAX.WORKING VOLTAGE	DC : 0~15KV DC AC : pulse ≦30KV peak to peak AC : Sine wave ≦10KV rms
SIGNAL / NOISE	≧60dB(1KHz), ≧50dB(1MHz)
BANDWIDTH	DC~50MHz(-3dB)
DIVISION RATIO	1 : 1000
RISE TIME	≦7ns
INPUT RESISTANCE	100MΩ± 0.5%
INPUT CAPACITANCE	3.0PF± 0.5PF
COMPENSATION RANGE	5PF~50PF
CABLE LENGTH	2.0METER(± 0.2M)
TEMPERATURE COFFICIENT	≦200PPM / ℃
DC ACCURACY	≦0.7%
SAFETY APP.	CE, GS, UL, CUL
OPERATING TEMPERATURE	0~50℃
STORAGE TEMPERATURE	-20~+70℃
WEIGHT / VOLUME	250g / φ75*340mmL.



IEC 1010
EN 61010

TECPEL CO., LTD.
No. 13, ALLEY 5, LANE 31, CHUNG-TEH STREET,
TAIPEI 110, TAIWAN, R.O.C.
Tel : (02) 2737-5866 Fax: 886-2-2737-3343
E-mail: sales@tecpel.com http://www.tecpel.com

※Specifications and appearance design subject to change without notice.